

**O300130**

## 5:1 Air Operated Oil Tank Pump



September 2019

**The Alemlube EL Series O300130 5:1 Air Operated Oil Tank Pump is ideal for dispensing oil with a maximum viscosity of SAE240.**

An excellent value for money proposition, the EL Series O300130 gives you the opportunity to upgrade from standard hand operated oil drum pumps to a pneumatic solution.

Delivering up to 18L/min the O300130 5:1 ratio oil tank pump is suitable for dispensing motor oil, synthetic oil, hydraulic oil, gear oil and automatic transmission fluid.

Smart design with fewer working parts effectively means less pump wear & tear and facilitates a lower cost of ownership.

Manufactured with efficiency and reliability in mind, the O300130 5:1 ratio oil tank pump is well designed, affordable and is supported by readily available spare parts.

### SPECIFICATIONS, FEATURES AND BENEFITS

- Effortless oil transfer
- Smart design with fewer moving parts
- Delivers up to 18L/min
- Maximum operating pressure of 750psi (50bar)
- Maximum oil viscosity of SAE240
- Air consumption of 2.8cfm at 80psi
- 1/2" BSP(m) oil outlet
- 1/4" BSP(f) air inlet connection
- Suction tube length of 270mm, diameter 42mm
- Inlet filter protects against foreign particle contamination
- 2" bung adaptor supplied standard
- Noise level of 82dB
- Saves time and increases productivity
- Low cost of ownership

