



CR30060

240V Electric Cable Reel - 15amp



June 2021

The Alemlube EL Series CR30060 240V electric cable reel is an innovative storage & retrieval system containing 20 metres of 3 x 2.5mm² cable, 15amp socket and plugs designed to provide a convenient, tidy and safe means of controlling electric cable in the workplace.

The robust plastic outer casing contains an automatic spring rewind mechanism featuring an adjustable safety retraction system that allows the cable to be conveniently stopped at any desired point and then efficiently rewinds the 20m cable for storage after use. The CR30060 can be mounted/demounted via the integral swivelling steel wall bracket.

Complete with 1.5m lead-in cable, the Alemlube EL Series CR30060 240V electric cable reel is a user friendly, compact reel complete with a thermal overload protection breaker.

A must for addressing safety in the workplace, it is recommended that the user must fully extend the electric cable prior to switching on mains power to avoid the cable over heating and possibly catching fire thus creating an unsafe, hazardous situation.

With a maximum power rating of 1,600W when the cable is coiled and 3,200W when uncoiled. The CR30060 240V electric cable reel is CE approved and Australian Standard compliant in accordance with AS/NZ5 3000 standard.

The Alemlube EL Series CR30060 240V electric cable reel is ideal for use with single phase gen sets, column lifts, TIG & MIG welding machines, heavy duty refrigeration & air conditioning equipment and a myriad of applications around the workshop.

SPECIFICATIONS, FEATURES AND BENEFITS

- P240V, maximum 15amp
- Supplied with 20m of 3 x 2.5mm² cable
- Maximum power when coiled is 1,600W, when uncoiled 3,200W
- Thermal overload protection
- Impact tested to IK08 with a top rating of IK10 possible
- Automatic and consistent speed control mechanism helps address WH&S concerns
- Durable construction with reel covers manufactured from high quality impact resistant polypropylene
- Swivelling steel wall bracket
- Ratchet stop device is easily inspected by the end user
- Australian Standard compliant in accordance with AS/NZ5 3000
- Indoor use only

