

454151AA Portable IBC Oil Filtration Kit



August 2019

The 454151AA Portable IBC Oil Filtration Kit has been designed to deliver clean oil filtered to ISO 16/13 cleanliness levels. Capable of recirculating oil in a “closed-loop” the unit cleans oil that is initially above this level and maintains oil in that condition prior to delivery to your equipment.

The unit can easily be adapted to existing workshop piping hose reel setup or can be fitted with optional Samoa 10m x ½” oil hose reel and Samoa metered oil nozzle in conjunction with Samoa brackets for both hose reel and nozzle, as shown in this product image for IBC use.

Operating with clean, dry air at 90psi, the Alemlube portable IBC filtration kit is suitable for use with multiple oil grades – SAE 10 hydraulic oil; SAE 15W-40 engine oil; SAE 30W transmission oil; SAE 50W drive train; 85W-140 gear oil.

The 454151AA is supplied inclusive of a Samoa 5:1 ratio oil stub pump & wall bracket, non-bypass filter head, 7 micron filter, drum breather, thermal valve, ¼” FRL + gauge, operating instructions and safety warning decals.

Investment in the Alemlube 454151AA is a smart move towards keeping machine fluids free from outside contaminants and saves money, reduces downtime and helps maintain productivity.

SPECIFICATIONS, FEATURES AND BENEFITS

- Samoa 5:1 ratio oil stub pump and wall bracket
- Samoa 10m x ½” oil hose reel (optional for IBC use)
- Samoa metered oil nozzle (optional for IBC use)
- Samoa meter bracket (optional for IBC use)
- IBC top mount bracket for hose reel (optional for IBC use)
- Suction/circulate pick up tube and connectors
- IBC lid with two ports for breather and circulation hose
- Moisture absorbing drum breather
- Non-bypass filter head
- 7 micron filter
- Filters oil to ISO 16/13 Cleanliness levels
- Filter mounting bracket
- Suitable for multiple oil grades
- Keeps fluids free from outside contaminants
- Wooden crate for shipping

