

AA22

Alemlube Automotive Tyre Changer



January 2019

The Alemlube Automotive AA22 Tyre Changer features a fully automatic pneumatic tilting column and a direct motor/gearbox drive ensuring reliability and a trouble free service life .

A stronger and more steady frame has been achieved by the unique trapezoid chassis design resulting in a stronger support for day in, day out tyre changing operations.

A patented O66 help arm system specifically designed for large, heavy duty and low profile tyres and further to this, the versatile bead breaker is adjustable in four positions that permits working on a larger variety of tyre and wheel combinations.

The Alemlube Automotive AA22 Tyre Changer has been manufactured with clamping jaws created by a totally one-step die casting method and performs internal clamping from 12" to 27" with external clamping from 10" to 25".

The AA22 accommodates wheels with a maximum wheel diameter of 45" (1143mm) and a maximum wheel width of 16" (406mm).

* Tyre changer depicted is fitted with the optional leverless mount/demount head

SPECIFICATIONS, FEATURES AND BENEFITS

- Trapezoid chassis design for stronger support
- O66 helper arm system for low profile tyres
- Bead breaker is adjustable in 4 positions
- Air supply pressure of 116-145psi (8-10bar)
- Direct motor and gearbox drive
- No belt between motor and gearbox
- Oiler, Filter and regulator included
- Motor speed of 7.5 cycles per minute
- Motor power of 0.55 / 0.75 / 1.1kw
- One-step die cast clamping jaws
- Internal clamping from 12" to 27"
- External clamping from 10" to 25"
- Noise level <75dB
- 240V 1Ph power supply
- Optional barrel type tyre inflator bead blaster available
- Optional leverless mount/demount head
- 240V (10amp) power supply