

SOP620 S Series Oxy Propane/LPG Hose Reel



March 2023

The new SOP620 Oxy Propane/LPG hose reel from Alemlube is a genuine industrial quality welding reel ideal for all general welding applications undertaken by contractors, fabricators and people involved in the construction and industrial fields.

Featuring impact resistant UV stabilised covers for maximum durability and an automatic and positive latching mechanism, the SOP620 can easily be mounted on the wall or ceiling and can be carried in Utes and service vehicles.

The heavy duty spring assembly retrieves the Grade T hose even when fully extended and the tension adjustability function enables the spring tension to be adjusted to suit each individual application. The SOP620 Oxy Propane/LPG hose reel from Alemlube has a maximum working pressure of 300psi (20bar), dimensions of 630 x 442 x 261mm and helps to comply with increasing WHS requirements enabling you to provide a safer working environment while at the same time increasing efficiency and productivity.

SPECIFICATIONS, FEATURES AND BENEFITS

- Maximum working pressure of 300psi (20bar)
- Complete with 15m of 6mm ID twin Grade T hoses & 0.9 lead in hose
- Lead in hose : 5/8" UNF(f) fitting
- -30°C - 60°C working temperature
- Automatic & positive latching system
- Impact resistant UV stabilised covers
- Adjustable spring tension
- Two piece hose stop enables quick & easy hose length adjustment
- Can be mounted on the wall, ceiling, in Utes & service vehicles
- Suitable for use with Oxy Acetylene & Oxy/LPG