

670AN5

20V Lithium-ion Cordless Grease Gun



June 2021

The 670AN5 20V Lithium-ion cordless grease gun from Alemilube is an innovative grease gun with built in intelligence and a powerful 4.0Ah battery as standard. The only cordless grease gun kit complete with charger and 4.0Ah battery on the market ready to go, the 670AN5 can dispense up to 35 x 450g cartridges per charge.

It's smart too. An LCD shows real time battery capacity, grease level, grease metering information, loss of priming and stall warning with the press of a button to assist the user in always being prepared to have a fully operational grease gun at hand to be active on the job.

Designed and engineered by Alemite USA, the 670AN5 is capable of developing a maximum operating pressure of 10,000psi (690 bar) facilitating fast, effortless greasing guaranteed and offers dual flow rates: high at 170 g/min, low at 113 g/min. Two Lithium-ion batteries are supplied with the 670AN5, 1 x 4.0Ah and 1 x 2.5Ah, with fast recharging so you'll never be without greasing power to complete your ongoing work.

Lightweight and ergonomic, the 670AN5 is supplied complete with a 900mm long grease gun flex, a heavy duty coupler and has the versatility of three way loading; 450g cartridge, bulk grease or filler pump. And, a skin version (670AN5-SKIN) without battery can also be purchased to assist in having varying grease grades on hand and ready to swap over or use the additional the battery.

Furthermore, a 400g version is also available as the 597F to suit all USA and European sized grease cartridges. Protected in a durable plastic moulded carry case, the 670AN5 20V Lithium-ion cordless grease gun provides you with an intelligent and trouble-free high pressure, high volume greasing solution.

SPECIFICATIONS, FEATURES AND BENEFITS

- Powerful 4.0Ah battery plus 2.5Ah spare battery supplied standard
- Delivery rates of up to 170 g/min
- Grease pressure of up to 10,000psi (690bar)
- Up to 35 cartridges per battery charge
- Dual flow rates: 113 g/min and up to 170 g/min
- LCD for real time battery capacity, grease level and grease metering
- Loss of priming and stall warning indication
- Fast recharger time of 2 hours, LED light with on/off control
- Suitable for use with grease up to NLGI2
- Three way loading: 450g cartridge, bulk grease or filler pump
- Ball and needle bearings
- Curved slot yoke optimises mechanical efficiency
- Case hardened piston for wear and bend resistance
- Impact resistant LCD lens surrounded by impact absorbing bezel
- Patented air flow management optimises motor and transmission life
- Shape, weight and balance designed for less physical strain
- Fast effortless greasing guaranteed

