



5080AN

Hi Flo Refuelling Drum Pump with Filter



January 2023

The 5080AN hi flo refuelling drum pump with filter has low torque, is easy to use and with little effort is capable of delivering up to 110 litres per minute or best in class delivery rates of 1.1 litres per rotation.

Supplied complete with an FA2N fuel filter, 2.6 metres of antistatic, UV & fuel resistant hose, spout, in built spout holster, 4-piece downtube and new heavy duty bung adaptor, the 5080AN also features a PPR covered handle grip designed to reduce operator fatigue during high volume fuel transfer.

The FA2N fuel filter features a 10 micron fuel filter element, a drain cock and a replaceable clear plastic bowl and a 1" BSP inlet and outlet.

Suitable for the fast and efficient transfer of diesel fuel, petrol, avgas, light oils up to SAE30 and kerosene, the 5080AN incorporates a lockable handle to help minimise the possibility of unauthorised fuel transfer.

SPECIFICATIONS, FEATURES AND BENEFITS

- Low torque, high volume easy to use pump delivers up to 110L/min
- Delivery rates of 1.1 litres per rotation
- Lockable handle minimises the possibility of unauthorised fuel transfer
- PPR covered handle grip reduces operator fatigue
- Rubber seal above the bung adaptor reduces fuel contamination
- Supplied complete with 2.6m of anti-static, UV and fuel resistant hose, spout, in built spout holster, 4-piece downtube, heavy duty bung adaptor
- FA2N fuel filter features a 10 micron fuel filter element, a drain cock and a replaceable clear plastic bowl with a 1" BSP inlet and outlet
- Steel springs on the hose assembly reduce the possibility of premature hose failure
- Suitable for the transfer of diesel fuel, petrol, Avgas, light oils up to SAE30 and kerosene

Also available **5060AN** without FA2 fuel filter

