

223003 Alemlube 205L Mobile Grease Transfer Kit



June 2021

The Alemlube 223003 is a 180kg mobile grease transfer kit consisting of a 55:1 ratio air operated grease transfer pump (409200) capable of delivery rates of up to 300g/min, a durable Alemlube S Series grease hose reel supplied complete and ready to use with 10m x 6mm ID delivery hose (SG800) with Samoa control valve (413080) and a sturdy 180kg drum trolley with two robust solid wheels plus two swivelling rear wheels ensuring ease of movement, stability and safety.

The 223003 is an economical, quality mobile grease transfer kit providing workshop flexibility by facilitating quick, efficient and effortless grease transfer in car, light commercial vehicle and truck & bus workshops.

The Samoa 55:1 pressure ratio pump has an air pressure operating range of 20 to 140 psi and is ideal for the transfer of grease up to NLGI2 specification.

The grease hose reel is manufactured from high quality impact resistant and UV stabilised polypropylene, features a positive latching system, heavy duty internal spring assembly and highly flexible S.A.E.100 R2 rubber hose with crimped hose ends.

The Samoa grease control valve is the perfect device at the end of the hose assembly to control grease delivery. Its lightweight ergonomically designed aluminium body delivers reliable performance in all applications.

SPECIFICATIONS, FEATURES AND BENEFITS

- Transfer kit delivery rates of up to 300g/min
- Suits 180kg drums
- Impact resistant heavy duty hose reel
- 10m x 6mm ID delivery hose
- 0.9m lead in hose
- Maximum fluid outlet pressure of 5,000psi (345 bar)
- Samoa grease control valve with rigid outlet
- Sturdy trolley with robust solid wheels

