



PRODUCT INFORMATION

May 2016 Update

PD10120

Petrol Driven 1" Diesel Transfer Pump

The Alemlube PD10120 petrol driven 1" transfer pump is specifically designed and manufactured for the transfer of diesel fuel. Mounted in a robust tubular steel roll frame with rubber feet the PD10120 is completely portable, suits many industrial, workshop, agricultural, municipal, marine services and on site refuelling applications and is capable of transferring up to 120 litres of diesel fuel per minute.

Driven by a powerful 1.5HP air cooled 2-stroke petrol engine this lightweight die-cast aluminium pump with 1" diameter inlet & outlet ports operates efficiently with a maximum suction head of 7 metres and a maximum lift head of 22 metres.

Always ready to perform tank filling or refuelling, the PD10120 has a run time of 1.0 hour at $\frac{3}{4}$ load, a 1.2L fuel tank capacity and is pull start ignition.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Flow rates of up to 120L/min

1.5HP air cooled 2-stroke petrol engine

1" (25mm) inlet & outlet ports

Fuel tank capacity of 1.2L

Recoil starting system

Run time (per tankful) at $\frac{3}{4}$ load of 1.0 hour

Maximum lift head of 22m

Maximum suction head of 7m

Dimensions: 390mm x 305mm x 340mm

Dry weight: 8kg

Pull start ignition

PETROL DRIVEN DIESEL TRANSFER PUMPS AVAILABLE

| | | | |
|------------|--------|------------|------------|
| PD10120 | 1" | Pull Start | 120 L/min |
| PD15300 | 1-1/2" | Pull Start | 300 L/min |
| PD20450 | 2" | Pull Start | 450 L/min |
| PD20450KS | 2" | Key Start | 450 L/min |
| PD301000 | 3" | Pull Start | 1000 L/min |
| PD301000KS | 3" | Key Start | 1000 L/min |
| PD401500 | 4" | Pull Start | 1500 L/min |
| PD401500KS | 4" | Key Start | 1500 L/min |

ORDERING INFORMATION

PD10120

Petrol Driven 1" Diesel Transfer Pump

