



Alemlube S SERIES HOSE REELS

The extended range of hose reels from Alemlube will provide you with a reliable and cost effective means of storing and retrieving hose assemblies in your workshop or garden.

- Quality impact resistant UV stabilised covers for maximum durability
- Detachable steel mounting bracket enables 180° hose reel rotation
- Automatic and positive latching mechanism
- Adjustable hose stop for convenient lead length positioning
- Can be wall, ceiling or floor mounted



| PART NO. | PRODUCT DESCRIPTION | HOSE LENGTH | HOSE ID | WORKING PRESSURE | HOSE MATERIAL | COVER COLOUR | HOSE COLOUR | MAX WORKING TEMP. | REEL INLET BSPT(m) | HOSE OUTLET BSPT(m) | WEIGHT |
|----------|-------------------------|-------------|---------|-------------------|---------------------|--------------|-------------|-------------------|--------------------|---------------------|--------|
| SA300N | AIR HOSE REEL | 18m | 10mm | 300 psi (20bar) | HYBRID POLYMER | RED | YELLOW | -10°C-60°C | 3/8" | 3/8" | 10kg |
| SA400N | AIR HOSE REEL | 15m | 12mm | 300 psi (20bar) | HYBRID POLYMER | RED | YELLOW | -10°C-60°C | 1/2" | 1/2" | 10kg |
| SAW100 | AIR AND WATER HOSE REEL | 16m | 10mm | 300 psi (20bar) | PVC | RED | BLUE | 0°C-60°C | 3/8" | 3/8" | 10kg |
| SAW200 | AIR AND WATER HOSE REEL | 13m | 12mm | 300 psi (20bar) | PVC | RED | BLUE | 0°C-60°C | 3/4" | 3/4" | 10kg |
| SW500N | WATER HOSE REEL | 18m | 12mm | 180 psi (20bar) | POLYURETHANE | BLUE | RED | -20°C-60°C | 1/2" | 1/2" | 10kg |
| SO600 | OXY-ACETYLENE HOSE REEL | 15m | 6mm | 300 psi (20bar) | RUBBER | BLUE | RED/BLUE | -30°C-60°C | 5/8" | 5/8" | 10kg |
| SGRW510 | GARDEN WATER HOSE REEL | 16m | 12mm | 145 psi (20bar) | PVC | GREEN | GREEN | 0°C-60°C | 3/4" | Nozzle | 10kg |
| SO1700 | OIL HOSE REEL | 10m | 12mm | 2,000 psi (20bar) | S.A.E. 100R1 RUBBER | BLACK | BLACK | -30°C-100°C | 1/2" | 1/2" | 15.6kg |
| SG800 | GREASE HOSE REEL | 10m | 6mm | 5,000 psi (20bar) | S.A.E. 100R2 RUBBER | BLACK | BLACK | -30°C-100°C | 1/4" | 1/4" | 15.6kg |

COMMERCIAL VEHICLE WHEEL SERVICE

GRS926 Ravaglioli Commercial Vehicle Tyre Changer

- Truck Tyre Changer for both roadside and workshop service, suitable for closed vans and/or small workshops.
- Handles rim size from 11" to 27"
- Hydraulic chucking table
- Hydraulic up-down movement
- Also suitable for agricultural tyres
- Manufactured in Italy



GTL4-140RC Ravaglioli Truck Wheel Balancer

- Versatile machine, designed for easy, fast & accurate balancing of commercial wheels
- Microprocessor controlled with self-calibration and self-diagnostics
- One single spin with low rotation speed provides all the values
- Complete with cones for trucks (Ø from 202 – 221mm & 281mm)



RAVTD8060/VARCOMBO Ravaglioli Combined Truck & Car Wheel Aligner

- First of its kind
 - Ravaglioli Truck & Car Wheel Aligner with cabinet, computer, printer, monitor, keyboard complete with car & truck database
 - Includes two pairs of STDA30E standard truck wheel clamps, two pairs of STDA95E 3 point car wheel clamps, one pair of STDA29L commercial turntables, one pair of S110A7 car turntables, 2 front measuring heads for trucks, 2 front measuring heads for cars, 2 rear measuring heads for cars & trucks and a modified cabinet to accept 6 measuring heads
 - Manufactured in Italy
- Note:** The VARCOMBO RAV option cannot be sold separately & must be ordered with the truck wheel aligner RAVTD8060TWSR and cannot be ordered at a later date to convert an existing truck aligner to perform car alignments



201220 240V IBC AdBlue® Dispensing Kit

- Includes a 1.5m suction hose pump to IBC mounting adaptor, 6m delivery hose
- Self contained on a stainless steel mounting bracket with nozzle holster, the kit is easily moved from one IBC to another
- Flow rates of up to 32L/min
- IBC not included



332080N AdBlue® Rotary Drum Pump

- Delivery rates of 380ml per rotation or up to 38L/Min
- Stainless steel and teflon construction ensures 100% compatibility with Adblue®
- Valving in the pump head facilitates self-priming with immediate and easy dispensing
- Supplied with 2.6m delivery hose, stainless steel spout and 2" trisure drum bung adaptor
- Also suitable for pumping water & antifreeze



RAV825.10 Ravaglioli 25t Commercial Vehicle Knuckle Lift

- 25t lifting capacity
- Long platform length of 10m
- Total length of 12.7m
- No cross rails or torsion bars between lifting platforms
- Electronic platform synchronisation, independent of load distribution
- Can be supplied for recessed installation
- Manufactured in Italy

RAV232NL Ravaglioli 22.0t 4-Post Column Lift

- Ideal lifting system for business, B-doubles, mobile cranes and workshops where space is an issue and workshop flexibility is required
- Large and solid base for maximum stability under load
- Lifting spindles in rolled steel with bronze main nut and safety nut
- Master column with a main control panel and slave column with a secondary control panel and emergency stop button combine to effect the vehicle's lifting and descent
- Fully mobile



NDP-15FPS AdBlue® 1/2" Diaphragm Pump

- 1/2" BSP(f) inlet and outlet ports
- Maximum flow rate of 45L/min
- 1/2" BSP(f) fluid inlet
- 1/4" BSP(f) air inlet
- 1/2" BSP(f) fluid outlet
- Also suitable for the transfer of waste oils, waste water, oil, pesticides and herbicides



RAV307H.4WS Ravaglioli Wireless 22.0t Electro-Hydraulic Mobile Column Lift

- Wireless 2.4 GHZ communication between columns
- Each column has a lifting capacity of 5,500 kg
- Handles tyre diameters from 900mm to 1,200mm with a minimum rim diameter of 580mm
- Each column powered by two 12V maintenance-free 100A/h gel type batteries



KP442NE Ravaglioli 14.0t 4-Post Vehicle Hoist

- Maximum access to the vehicle is provided due to the unique feature of extended platforms
- A safety micro-switch is activated after main nut failure and the electro-mechanical safety system ensures perfect horizontal lifting of the platforms and a balanced load on the motors regardless of vehicle position
- Ideal for transport companies, fleet owners, government authorities, mine site and workshops
- Other larger and smaller 4-post commercial vehicle hoists available upon request

20077 LED Slimline Work Light

- 6W COB LED, min-max 250-600lm
- 3W SMD top LED, 120lm
- 80 CRI, 6500K
- 3.7V 2600mAh Li-ion battery
- 5.5 / 2.5 hour main light runtime
- 10.0 hour top light runtime
- 4 hour charge time
- IP54 foreign objects / moisture intrusion rating
- IK07 impact resistance rating



20066N2 LED Work Light with Aircon Gas Leak Detection Capabilities

- Gas leak detection capabilities
- 4W COB LED, 400lm on body
- 3W SMD LED, 100lm on top
- 80 CRI to illuminate true colours
- 3.7V 2200mAh Li-ion battery
- 3 hour main light run time
- 10 hour top light run time
- 28 hour top UV light run time
- 3.5 hour charge time
- 180° adjustable handle
- 3 strong magnets
- 2 foldaway hanging hooks




SJ-100-002 2 Drum Spill Container

- Holds up to 2 x 205L drums
- 100% recyclable polyethylene construction
- Non-skid removable deck
- Compatible with most forklifts and pallet trucks
- Sump capacity of 236L
- Dimensions of 750mm (L) x 1,300mm (W) x 440mm (H)
- Weight of 20kg
- Drums not included
- SJ-110-006 as above but for 4 drums



SJ-510-001 IBC Spill Container

- 100% recyclable polyethylene construction
- Cannot rust or corrode
- Capacity of 1,180L
- Compatible with most forklifts and pallet trucks
- Can be used with or without a deck
- Dimensions of 1,680mm (L) x 1,680mm (W) x 700mm (H)
- IBC not included
- SJ-520-001 as above but for a double IBC



SJ-300-006 4 Drum Workfloor & Spill Container

- Slip resistant texture on workfloor deck and ramp
- Cannot rust or corrode
- Excellent chemical compatibility
- Sump capacity of 240L
- Dimensions of 1,600mm (L) x 1,600mm (W) x 150mm (H)
- Weight of 45kg
- Drums not included



504250 Twin Pedestal Oil Hose Reel

- Maximum working pressure of 2,300psi (160bar)
- 1/2" BSP(m) inlet/outlet
- Supplied complete with 15m x 1/2" ID R1 hose and 0.8m inlet hose
- Full 1/2" ID port, shaft and swivel
- Narrow footprint measuring 168mm wide
- Heavy duty double pedestal construction



Head Office
Phone: 02 9938 2999
Fax: 02 9938 6605

New South Wales
Phone: 02 9677 1555
Fax: 02 9675 1155

Victoria / Tasmania
Phone: 03 8787 8288
Fax: 03 8787 8266

www.alemlube.com.au
info@alemlube.com.au
www.alemlube.co.nz
info@alemlube.co.nz



*Applies to all products unless indicated otherwise
Specifications subject to change without prior notice
RP-AG-2020 Alemlube Pty Ltd

Queensland/ PNG
Phone: 07 3204 9166
Fax: 07 3204 1224

Mackay Queensland
Phone: 0425 277 706
Fax: 07 3204 1224

Western Australia
Phone: 08 9302 4199
Fax: 08 9303 209

Automotive Head Office (VIC)
Phone: 03 8768 8011
Fax: 03 8768 8049

South Australia / Northern Territory
Phone: 08 8241 7111
Fax: 08 8241 7011

New Zealand
Phone: 64 9 447 1007
Fax: 64 9 447 1008



660AN
Trigger Action Grease Gun

- Grease pressures of up to 8,500psi (586bar)
- Delivers up to 1.1g of grease per stroke
- High volume/high pressure option
- Coarse thread on the barrel assembly eliminates cross threading during cartridge changeover
- Twin Lock System seals the piston and eliminates the possibility of dummy lubrication



600A
Lever Action Grease Gun

- Develops grease pressures of up to 12,000psi (828bar)
- Delivers up to 1.6g of grease per stroke
- Twin Lock System eliminates the possibility of dummy lubrication
- Ever-Flow System enables the gun to be used with thick tacky greases even in the coldest conditions
- High volume, high pressure greasing guaranteed



670AN5
20V Lithium-ion Cordless Grease Gun

- Delivery rates of up to 170g/min (high) & 113g/min (low)
- Grease pressures of up to 10,000psi (690bar)
- Up to 35 cartridges per battery charge
- Built in Intelligence
- LCD with real time battery capacity, grease level and grease metering information
- Delivery rate and pressure adjustable
- Ball and needle bearings



680AN
Air Operated Grease Gun

- Pressure ratio of 40:1
- Develops grease pressures of up to 3,920psi (270bar)
- Delivers up to 180 g/min
- Suits 450g cartridge or bulk grease
- Recommended maximum air pressure of 98psi (7bar)
- Continuous flow or single shot operation

G10040N
EL Series 18V Lithium-ion Cordless Grease Gun

- Generates grease pressures up to 10,000psi (690bar)
- Delivery rates of up to 80g/min
- 25 minutes continuous working time
- Recharge time of 75 minutes (1,500 mAh battery)
- Spare battery, recharger, 106cm long grease gun flex and plastic molded carry case supplied standard
- The key to fast and efficient plant and machinery greasing



428262
180kg Air Operated Grease Kit

- 55:1 ratio grease pump develops up to 7,950psi (548bar)
- Integral filter eliminates the chance of pump tube contamination
- Lightweight ergonomic, cast alloy, grease control valve included
- 180kg drum not included



424170
20kg Grease Kit

- Integral filter protects pump from foreign particle contamination
- Delivery rates of up to 0.9kg/min
- 55:1 ratio air motor develops grease pressures of up to 7,950psi (548bar)
- Will handle high density, tacky greases up to NLGI2
- 424150 as above but with trolley



ILC MAX-20
Automatic Grease Lubrication System

The ALEMLUBE ALS system is a easy to install automatic lubrication system featuring high performance, reliability and rugged design. With its high pressure output the ALEMLUBE ALS system can service grease points within a radius of up to 30m. The ALEMLUBE ALS system uses precision progressive dividers to ensure accurate and reliable lubricant distribution to all connected grease points, with built in indication if any grease point refuses to take grease. Suitable for transport, construction, mining, agriculture, manufacturing, food & beverage and waste management.

52004A
High Volume 12V Diesel Refuelling Drum Pump

- Flow rates of up to 68 L/min
- 1" BSP(f) inlet and outlet threads
- Duty cycle of 30 minutes on and 30 minutes off
- Telescopic down tube suits fuel tanks up to 1,000mm deep
- Motor protection fuse prevents motor overload
- Suitable for diesel fuel transfer only
- 52004 as above but with a manual nozzle



5060AN
Hi-Flow Refuelling Drum Pump

- Low torque, high volume pump is easy to use and delivers up to 110L/min
- Facilitates best in class delivery rates of 1.1 litres per rotation
- Lockable handle minimises the possibility of unauthorised fuel transfer
- Suitable for the transfer of diesel fuel, petrol, light oils up to SAE30 and kerosene
- Supplied complete with 2.6m of UV and fuel resistant hose, spout, in built spout holster, 3-piece downtube and new heavy duty bung adaptor



501A
Rotary Drum Pump

- Zinc alloy impellers make the pump suitable for the transfer of diesel, petrol, kerosene, unleaded petrol and low viscosity oils
- Delivery rates of 18L/min or 0.26L per rotation
- Includes 2.2m of antistatic hose, bung adaptor, rubber gasket, four chamber rotor assembly, spout and spout holster



Alemlube
Lockable Diesel Refuelling Storage & Dispensing Kits

- Unique user friendly design with lockable lid to aid fuel and dispensing kit security
- Dispensing kit consists of a 12V pump, 4m antistatic fuel delivery hose, 2m battery cables and automatic nozzle
- Recesses for tie down straps and internal baffles are valuable safety features
- Forklift lifting point capability

| Product No. | Capacity | Flow Rate | w/ Meter |
|-------------|----------|-----------|----------|
| L60040PAM | 600L | 50 L/min | Yes |
| L60040PA | 600L | 50 L/min | — |
| L45040PAM | 450L | 50 L/min | Yes |
| L65040PA | 450L | 50 L/min | — |
| L20040PAM | 200L | 50 L/min | Yes |
| L20040PA | 200L | 50 L/min | — |
| L10040PAM | 100L | 50 L/min | Yes |
| L10040PA | 100L | 50 L/min | — |



L40040PA
400L Lockable Diesel Refuelling Storage & Dispensing Kit

- Dispensing kit consists of a 12V pump, 4m antistatic fuel delivery hose, 2m battery cables and automatic nozzle
- Delivery rates of up to 50L/min
- Polyethylene tank weighing just 32kg - cannot dent, scratch or corrode
- Tank dimensions: 1,165mm (W) x 1,165mm (D) x 566mm (H)




51040
Automatic Diesel Nozzle

- Automatically cuts off when a diesel tank is full
- Suitable for applications involving electric diesel transfer pump
- 1" BSP swivel included
- Flow rates up to 140L/min

14500 Series
Quick Release Grease Gun Couplers

- Works with all grease gun types - pneumatic, manual and battery
- Maximum working pressure of 10,000psi (690 bar)
- Lock-on and free up both hands to operate your grease gun
- Easy disconnection regardless of hydraulic pressure build up
- Suitable for high pressure, heavy duty greasing applications
- 14512 1/8" BSP(f) 90mm long
- 14510 1/8" BSP(f) 135mm long
- 14511 1/8" NPT(f) 90mm long



454110N
Oil Transfer Kit With Meter

- Includes a high quality 3:1 ratio pump, 3m x 1/2" ID hydraulic hose and an electronic resettable meter
- Transfer rates of up to 12L/min
- 3/4" BSP(f) material outlet
- 1/4" BSP(f) air inlet
- Suitable for engine, gear, diff and hydraulic oils
- Suits 60L or 205L drums



8828N2
20L Gear Oil Drum Pump

- Capable of delivering up to 110mL on the downstroke
- Downtube extension and extra Rieke adaptor make the pump suitable for use with a variety of 20L drums available on the market
- Ideal pump for the transfer of engine, gear, diff and hydraulic oils in busy vehicle servicing workshops
- Drainback nozzle holster ensures that excess oil ends up back in the drum



99 Series
Spring Operated Drum Pumps

- Ideal for the topping up of engines, gear boxes, transmissions and differentials
- Spring operated pump and lever action control valve facilitates semi automatic lubricant and ATF transfer
- Unique swivelling pump head assembly

| Product No. | Description | Delivery Per Stroke | Drum Size |
|-------------|------------------------|---------------------|-----------|
| 9978 | 60L gear oil drum pump | 500mL | 60L |
| 9976 | 60L ATF drum pump | 500mL | 60L |
| 9928 | 20L gear oil drum pump | 330mL | 20L |
| 9926 | 20L ATF oil drum pump | 330mL | 20L |



454111N
Oil Transfer Kit with On/Off Gun

- Includes a high quality 3:1 ratio pump, 3m x 1/2" ID hydraulic hose and on/off control valve
- Transfer rates of up to 15L/min
- Suitable for engine, gear, diff and hydraulic oils
- Lubricant transfer and metering made easy



365534
Electronic Oil Meter

- Electronically meters and totalises the amount of lubricant dispensed
- Maximum flow rate of 30L/min
- Fluid inlet is a 1/2" BSP(f) swivel
- Runs with standard AAA batteries
- Maximum operating pressure of 1,450psi (100bar)
- Accurate to ± 0.5%



360160
Hose Reel Gantry

- Designed to mount up to six open-type or enclosed-type hose reels in a bank
- Ideal for servicing multiple workshop bays simultaneously
- Includes paper roll support, drip collector tray and two drawers with lock
- Dimensions: 2,400mm x 1,200mm x 310mm
- Hose reels and control valves not included



030060
EL Series Mobile 205L Oil Transfer Kit with Meter & Trolley

- 3:1 ratio air operated oil pump
- Flow rates of up to 10L/min
- Maximum operating pressure of 450psi (30bar)
- High mobility kit complete with 3:1 ratio oil pump, 1/2" ID hydraulic hose, electronic oil meter, 2" bung adaptor to suit 205L drums & robust trolley
- 030070 as above but with hose reel



454600N
Stationary Oil Pump, Reel and Meter Kit

- Includes a 3:1 ratio drum pump, 10m hose reel, electronic meter and a 2m pump to hose reel connection hose
- 3:1 ratio pump suits 205L drums
- Adjustable flow rates of up to 10L/min
- Electronic resettable oil meter is powered by easy to replace AAA batteries
- Dual pedestal hose reel withstands angular hose pull

51008
Mechanical Diesel Meter

- Accurate between flow rates of 20L/min to 120L/min
- Accurate to ±1.0%
- Maximum working pressure of 145psi (10bar)
- 1" BSP(f) inlet and outlet ports
- Batch total of 999L displayed with easy to read 18mm high digits
- Suitable for the metering of diesel and biodiesel
- 51007 as above but with a maximum batch total of 9,999L



365300
Electronic Preset Oil Meter

- Automatically cuts off when the preset amount of lubricant is dispensed
- Maximum flow rate of 30L/min, minimum flow rate of 1L/min
- 1/2" BSP(f) swivel supplied standard
- Can automatically meter from 99.9L and includes a totaliser
- Maximum operating pressure of 994psi (69bar)
- Accurate to ±0.5%



454695C
IBC Oil Storage & Transfer Kit

- Includes 1,000L IBC container, 3:1 ratio pump, dual pedestal hose reel with 10m of hose, a top mounting bracket and electronic oil meter
- Refillable, reusable, mobile and fully transportable
- 3:1 ratio pump facilitates flow rates of up to 18L/min
- Dual pedestal hose reel provides a long service life
- Electronic oil meter powered by quickly and easily replaceable AAA batteries
- 454697C as above but side mounts on an IBC



B.SMART
B.SMART Fuel Management

- No software installation required; cloud based
- Suitable for fleets of all sizes
- Real time feedback from wherever the site may be
- One software servicing multiple sites
- Transaction details are transferable and available
- Open one web page and select the required
- Suitable for diesel dispensing in agriculture, automotive, mining, construction, transport, logistics and industrial sectors



ALE-25BAH
1" Air Operated Diaphragm Pump

- Aluminium body and hytel diaphragms
- 1" BSP(f) inlet and outlet ports
- Flow rates of up to 160L/min
- Optimal stroke length maximises diaphragm life and performance with minimal downtime and maintenance costs
- Suitable for the transfer of diesel fuel, gear oil, engine oil, brake fluid, waste oil, waste water and antifreeze
- Teflon and stainless steel models also available



ALE-20BAH
3/4" Air Operated Diaphragm Pump

- Maximum flow rates of 100L/min
- 3/4" BSP(f) inlet and outlet ports
- Aluminium body and hytel diaphragms
- Rugged bolted construction eliminates leaks and simplifies post maintenance reassembly
- Maximum delivery per cycle of 350mL
- Light weight at 9kg
- Mounting hole layout of 140mm x 195mm
- Suitable for the transfer of diesel fuel, gear oil, engine oil, antifreeze, waste oil and waste water
- Dimensions of 249mm (W) x 319mm (H) x 180mm (D)



42100
Commercial Vehicle Mobile Waste Oil Drainer

- Holding tank capacity of 68L
- Holding tank capacity of 100L
- Sturdy and durable construction
- 145mm high swiveling front rubber wheels facilitate accurate mobility
- Internal baffles reduce the possibility of waste oil spillage
- Ideal for busy truck and bus workshops
- 860mm handle length
- Dimensions: 1,200mm (L) x 645mm (W) x 200mm (D)

PUMPS