

A14504 90° Grease Gun Coupler



December 2022

The Alemlube A14504 90° Grease Gun Coupler is an industrial quality grease gun coupler cleverly designed to assist in reaching difficult to access hydraulic grease nipples.

The rubber seal incorporated in the A14504 fits all SAE and metric hydraulic grease nipples and its four strong hardened steel jaws fit snugly to most grease nipples found on fixed plant machinery and mobile equipment.

Conveniently packaged in a carded blister pack, the A14504 can be prominently displayed at the sales counter or grease nipples display board to attract maximum customer attention and incremental impulse sales.

The Alemlube A14504 90° Grease Gun Coupler fits most standard grease guns and is the ideal accessory to have on hand in the workshop and in the field for when those tricky and hard to reach greasing jobs arise.



SPECIFICATIONS, FEATURES AND BENEFITS

- Industrial quality grease gun coupler suitable for standard hydraulic grease nipples
- 1/8" BSP(f) thread
- Fits most grease gun types: manual, pneumatic and battery powered grease guns
- Compact design enables access to difficult to reach lube points
- Rubber seal fits all SAE and metric grease nipples
- Recommended working pressure of 6,000psi (414bar)
- Burst pressure of 15,000psi (690bar)
- Length of 39mm
- Package measures 110mm x 70mm

Other blister packs available:

- A14506** Button head pull-on grease gun coupler - BSP
- A14507** Button head push-on grease gun coupler - BSP
- A14508** Right angle grease gun coupler - BSP
- A14510** 135mm long quick release grease gun coupler - BSP
- A14511** 90mm long quick release grease gun coupler - NPT
- A14512** 90mm long quick release grease gun coupler - BSP
- A14513** Standard duty 4 jaw grease gun coupler - BSP
- A14514** Standard duty 3 jaw grease gun coupler - BSP
- A14519** 135mm long quick release grease gun coupler - NPT